

KOMATSU BULLDOZERE D D85A-18 CUMMINS NT855 (26001->)



MOTOR Cummins NT855
Kapacitet: 43 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 250 timer/ 6 måneder

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 250 timer/ 6 måneder

SLUTDREV

Kapacitet: 36 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 30

HYDRAULIKSYSTEM PLANERINGSMASKINE MED SKRÅTSTILLET SKOVL

Kapacitet: 110 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 2000 timer

HYDRAULIKSYSTEM PLANERINGSMASKINE MED TIPPEANORDNING

Kapacitet: 110 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 2000 timer

KOMATSU BULLDOZERE D D85A-18 CUMMINS NT855 (26001->)



KØLESYSTEM

Kapacitet: 79 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

STYRING KOBLINGSHUS

Kapacitet: 122 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gear Oil Alcat 30

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.