

KOMATSU BULLDOZERE D D85EX-18 EO

KOMATSU SAA6D125E-5 STAGE IIIA/TIER 3



MOTOR Komatsu SAA6D125E-5
Kapacitet: 38 liter (Servicepåfyldning), Kapacitet: 47 liter (Tør efterfyld)

ANVEND

Normal (foretrukne)

KLIMA

Moderat

PRODUKTANBEFALING 1

Dieselfleet MSP 10W-30

PRODUKTANBEFALING 2

Dieselfleet MSP 15W-40

Skift alle 500 timer

GEAR Komatsu Torqflow 3/3
Kapacitet: 60 liter (Servicepåfyldning), Kapacitet: 90 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gear Oil Alcat 30

Skift alle 1000 timer

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

Skift alle 1000 timer

SLUTDREV

Kapacitet: 26 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 30

Skift alle 1000 timer

HYDRAULISK SYSTEM

Kapacitet: 69 liter (Servicepåfyldning), Kapacitet: 150 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

PRODUKTANBEFALING 2

Perlus H 46

Skift alle 2000 timer

KOMATSU BULLDOZERE D D85EX-18 EO

KOMATSU SAA6D125E-5 STAGE IIIA/TIER 3



SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 69 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15+	Coolant SP 12	

DÆMPERHUS

Kapacitet: 1,6 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gear Oil Alcat 30		

Skift alle 2000 timer

RULLER

Kapacitet: 0,35 liter (hvert)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gear Oil Alcat 30		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.