

KOMATSU DUMPERE MED LARVEBÅND CD

CD60R-1 S/N 2012 ->



MOTOR Komatsu S6D102

Kapacitet: 19 liter (Efterfyld), Kapacitet: 21,3 liter (Tør efterfyld)

ANVEND

Foretrukne

KLIMA

Moderat

PRODUKTANBEFALING 1

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2

Multifleet SHPD 15W-40

Skift alle 250 timer/ 6 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Dieselfleet MSP 15W-40

Skift alle 250 timer/ 6 måneder

HYDRAULISK SYSTEM

Kapacitet: 65 liter, Kapacitet: 45 liter (Efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Dieselfleet MSP 15W-40

PRODUKTANBEFALING 2

Gear Oil Alcat 10W

PRODUKTANBEFALING 3

Perlus H 46

Skift alle 2000 timer

SMØREPUNKTER/NIPLER

ANVEND

Foretrukne

KLIMA

Moderat

PRODUKTANBEFALING 1

Q11 Xtreme Duty Grease EP 2

Skift alle 100 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Skift alle 100 timer

KOMATSU DUMPERE MED LARVEBÅND CD CD60R-1 S/N 2012 ->



KØLESYSTEM

Kapacitet: 20 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

DÆMPERHUS

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 30

Kontroller alle 2000 timer

KØREREDUKTIONSENHED

Kapacitet: 2,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 250 timer, skift alle 500 timer

SVINGREDUKTIONSENHED

Kapacitet: 1,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 30

Kontroller alle 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.