

KOMATSU GAFFELTRUCK, DIESEL FD FD18H-IE



MOTOR Perkins KR104-22

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Synfleet SHPD 10W-40

Skift alle 200 timer

TRANSAKSEL

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Skift alle 6 måneder/ 1200 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Skift alle 200 timer

HYDRAULISK SYSTEM

ANVEND

Normal

KLIMA

Tropisk

PRODUKTANBEFALING 1

Perlus H 68

Skift alle 6 måneder/ 1200 timer

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Perlus H 46

Skift alle 6 måneder/ 1200 timer

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Perlus H 22

Skift alle 6 måneder/ 1200 timer

KOMATSU GAFFELTRUCK, DIESEL FD FD18H-IE



ANVEND		KLIMA
Første Service		Tropisk
PRODUKTANBEFALING 1		
Perlus H 68		

Skift alle 200 timer

ANVEND		KLIMA
Første Service		Middelhavsagtigt
PRODUKTANBEFALING 1		
Perlus H 46		

Skift alle 200 timer

ANVEND		KLIMA
Første Service		Koldt
PRODUKTANBEFALING 1		
Perlus H 22		

Skift alle 200 timer

HYDRAULISK BREMSESYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Skift alle 6 måneder/ 1200 timer

HEJSEKÆDER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
HDX 30		

HJULNAVSLEJER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KOMATSU GAFFELTRUCK, DIESEL FD FD18H-IE



NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

RULLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

RYKKEKONTROL

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.