

# KOMATSU GAFFELTRUCKS, DIESEL - BX50-SERIEN -16/17 FD20TUS-16 KOMATSU 4D94LE TIER 2 (200001A ->)



**MOTOR** Komatsu 4D94LE  
Kapacitet: 7,5 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Synfleet SHPD 10W-40**

PRODUKTANBEFALING 2

**Multifleet SHPD 10W-40**

Kontroller alle 8 timer, skift alle 1 måneder/ 200 timer

**DIFFERENTIALE**  
Kapacitet: 6 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

Kontroller alle 1 måneder/ 200 timer, skift alle 6 måneder/ 1200 timer

**TORQFLOW-TRANSMISSION** Torqflow  
Kapacitet: 9,6 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**ATF Dexron II-D**

Kontroller alle 1 måneder/ 200 timer, skift alle 6 måneder/ 1200 timer

**HYDRAULISK SYSTEM**  
Kapacitet: 55 liter (Hydrauliktank)

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Perlus H 32**

PRODUKTANBEFALING 2

**Perlus AF 32**

Kontroller alle 8 timer, skift alle 6 måneder/ 1200 timer

**HYDRAULISK BREMSESYSTEM**  
Kapacitet: 0,15 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Drauliquid DOT 3**

Kontroller alle 8 timer, skift alle 6 måneder/ 1200 timer

# KOMATSU GAFFELTRUCKS, DIESEL - BX50-SERIEN -16/17 FD20TUS-16 KOMATSU 4D94LE TIER 2 (200001A ->)



## SMØREPUNKTER/NIPLER

| ANVEND               |                                 | KLIMA                        |
|----------------------|---------------------------------|------------------------------|
| Normal               |                                 | Moderat                      |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

## KØLESYSTEM

Kapacitet: 9,2 liter

| ANVEND                |                      | KLIMA   |
|-----------------------|----------------------|---------|
| Normal                |                      | Moderat |
| PRODUKTANBEFALING 1   | PRODUKTANBEFALING 2  |         |
| <b>Coolant SP 15+</b> | <b>Coolant SP 12</b> |         |

*Kontroller alle 8 timer, skift alle 12 måneder/ 2400 timer*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*