

# KOMATSU GAFFELTRUCKS, DIESEL - TUSK CX20-SERIEN 800/900/1000/1100 1100PD2-8 KOMATSU S6D102E TIER 2



**MOTOR** Komatsu S6D102E-1  
Kapacitet: 15,1 liter

| ANVEND                                  | KLIMA            |
|-----------------------------------------|------------------|
| Normalt brændstof med lavt svovlindhold | Middelhavsagtigt |

|                          |  |  |
|--------------------------|--|--|
| PRODUKTANBEFALING 1      |  |  |
| <b>Multifleet SCD 30</b> |  |  |

Kontroller alle 8 timer, skift alle 1 måneder/ 200 timer

| ANVEND                                  | KLIMA   |
|-----------------------------------------|---------|
| Normalt brændstof med lavt svovlindhold | Moderat |

|                           |  |  |
|---------------------------|--|--|
| PRODUKTANBEFALING 1       |  |  |
| <b>Multifleet SCD 10W</b> |  |  |

Kontroller alle 8 timer, skift alle 1 måneder/ 200 timer

| ANVEND         | KLIMA            |
|----------------|------------------|
| Første Service | Middelhavsagtigt |

|                          |  |  |
|--------------------------|--|--|
| PRODUKTANBEFALING 1      |  |  |
| <b>Multifleet SCD 30</b> |  |  |

Skift alle 1 måneder/ 200 timer

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

|                           |  |  |
|---------------------------|--|--|
| PRODUKTANBEFALING 1       |  |  |
| <b>Multifleet SCD 10W</b> |  |  |

Skift alle 1 måneder/ 200 timer

# KOMATSU GAFFELTRUCKS, DIESEL - TUSK CX20-SERIEN 800/900/1000/1100 1100PD2-8 KOMATSU S6D102E TIER 2



## DIFFERENTIALE

Kapacitet: 13 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Kontroller alle 3 måneder/ 600 timer, skift alle 6 måneder/ 1200 timer

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Arktisk |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 |  |
|---------------------|---------------------|--|
| <b>SP Gear 5015</b> | <b>SP Gear 1071</b> |  |

Kontroller alle 3 måneder/ 600 timer, skift alle 6 måneder/ 1200 timer

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Skift alle 1 måneder/ 200 timer

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Arktisk |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 |  |
|---------------------|---------------------|--|
| <b>SP Gear 5015</b> | <b>SP Gear 1071</b> |  |

Skift alle 1 måneder/ 200 timer

## GEAR POWERSHIFT Torqflow

Kapacitet: 16 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1    |  |  |
|------------------------|--|--|
| <b>ATF Dexron II-D</b> |  |  |

Kontroller alle 200 timer, skift alle 6 måneder/ 1200 timer

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1    |  |  |
|------------------------|--|--|
| <b>ATF Dexron II-D</b> |  |  |

Skift alle 1 måneder/ 200 timer

# KOMATSU GAFFELTRUCKS, DIESEL - TUSK CX20-SERIEN 800/900/1000/1100 1100PD2-8 KOMATSU S6D102E TIER 2



## HYDRAULISK SYSTEEM

Kapacitet: 55 liter

| ANVEND              |                     | KLIMA   |
|---------------------|---------------------|---------|
| Normal              |                     | Moderat |
| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 |         |
| <b>Perlus H 32</b>  | <b>Perlus AF 32</b> |         |

Kontroller alle 8 timer, skift alle 6 måneder/ 1200 timer

| ANVEND              |                     | KLIMA   |
|---------------------|---------------------|---------|
| Første Service      |                     | Moderat |
| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 |         |
| <b>Perlus H 32</b>  | <b>Perlus AF 32</b> |         |

Skift alle 1 måneder/ 200 timer

## HYDRAULISK BREMSESYSYSTEM

Kapacitet: 0,15 liter

| ANVEND                  |  | KLIMA   |
|-------------------------|--|---------|
| Normal                  |  | Moderat |
| PRODUKTANBEFALING 1     |  |         |
| <b>Drauliquid DOT 3</b> |  |         |

Kontroller alle 8 timer, skift alle 6 måneder/ 1200 timer

## SMØREPUNKTER/NIPLER

| ANVEND               |                                 | KLIMA                        |
|----------------------|---------------------------------|------------------------------|
| Normal               |                                 | Moderat                      |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

## KØLESYSTEM

Kapacitet: 14 liter

| ANVEND                        |                     | KLIMA   |
|-------------------------------|---------------------|---------|
| Normal                        |                     | Moderat |
| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2 |         |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>  |         |

Kontroller alle 8 timer, skift alle 12 måneder/ 2400 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.