

KOMATSU GAFFELTRUCKS, DIESEL - TUSK CX20-SERIEN 800/900/1000/1100 900PD2-8 KOMATSU S6D102E TIER 2



MOTOR Komatsu S6D102E-1
Kapacitet: 15,1 liter

ANVEND	KLIMA
Normalt brændstof med lavt svovlindhold	Middelhavsagtigt

PRODUKTANBEFALING 1		
Multifleet SCD 30		

Kontroller alle 8 timer, skift alle 1 måneder/ 200 timer

ANVEND	KLIMA
Normalt brændstof med lavt svovlindhold	Moderat

PRODUKTANBEFALING 1		
Multifleet SCD 10W		

Kontroller alle 8 timer, skift alle 1 måneder/ 200 timer

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1		
Multifleet SCD 30		

Skift alle 1 måneder/ 200 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1		
Multifleet SCD 10W		

Skift alle 1 måneder/ 200 timer

KOMATSU GAFFELTRUCKS, DIESEL - TUSK CX20-SERIEN 800/900/1000/1100 900PD2-8 KOMATSU S6D102E TIER 2



DIFFERENTIALE

Kapacitet: 13 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 3 måneder/ 600 timer, skift alle 6 måneder/ 1200 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	SP Gear 1071	

Kontroller alle 3 måneder/ 600 timer, skift alle 6 måneder/ 1200 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 1 måneder/ 200 timer

ANVEND	KLIMA
Første Service	Arktisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	SP Gear 1071	

Skift alle 1 måneder/ 200 timer

GEAR POWERSHIFT Torqflow

Kapacitet: 16 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
ATF Dexron II-D		

Kontroller alle 200 timer, skift alle 6 måneder/ 1200 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1		
ATF Dexron II-D		

Skift alle 1 måneder/ 200 timer

KOMATSU GAFFELTRUCKS, DIESEL - TUSK CX20-SERIEN 800/900/1000/1100 900PD2-8 KOMATSU S6D102E TIER 2



HYDRAULISK SYSTEEM

Kapacitet: 55 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 32	Perlus AF 32	

Kontroller alle 8 timer, skift alle 6 måneder/ 1200 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 32	Perlus AF 32	

Skift alle 1 måneder/ 200 timer

HYDRAULISK BREMSESYSYSTEM

Kapacitet: 0,15 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Drauliquid DOT 3		

Kontroller alle 8 timer, skift alle 6 måneder/ 1200 timer

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 14 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Kontroller alle 8 timer, skift alle 12 måneder/ 2400 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.