

KOMATSU GAFFELTRUCKS, DIESEL - TUSK DX20-SERIEN 1800PD-8 KOMATSU SA6D102E (46001 ->)



MOTOR Komatsu SA6D102E-1
Kapacitet: 16,5 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Kontroller alle 8 timer, skift alle 1 måneder/ 200 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Multifleet SCD 10W	

Kontroller alle 8 timer, skift alle 1 måneder/ 200 timer

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Skift alle 1 måneder/ 200 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Multifleet SCD 10W	

Skift alle 1 måneder/ 200 timer

DIFFERENTIALE FOR
Kapacitet: 12,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Kontroller alle 3 måneder/ 600 timer, skift alle 6 måneder/ 1200 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 1 måneder/ 200 timer

KOMATSU GAFFELTRUCKS, DIESEL - TUSK DX20-SERIEN 1800PD-8 KOMATSU SA6D102E (46001 ->)



GEAR POWERSHIFT Torqflow Kapacitet: 20 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Multifleet SCD 10W		

Kontroller alle 1 måneder/ 200 timer, skift alle 6 måneder/ 1200 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1		
Multifleet SCD 10W		

Skift alle 1 måneder/ 200 timer

HYDRAULISK SYSTEM Kapacitet: 65 liter (Hydrauliktank)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Multifleet SCD 10W		

Kontroller alle 8 timer, skift alle 6 måneder/ 1200 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1		
Multifleet SCD 10W		

Skift alle 1 måneder/ 200 timer

HYDRAULISK BREMSESYSTEM Kapacitet: 0,05 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Drauliquid DOT 3		

Kontroller alle 8 timer, skift alle 6 måneder/ 1200 timer

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KOMATSU GAFFELTRUCKS, DIESEL - TUSK DX20-SERIEN 1800PD-8 KOMATSU SA6D102E (46001 ->)



KØLESYSTEM

Kapacitet: 17 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Kontroller alle 8 timer, skift alle 6 måneder/ 1200 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.