

KOMATSU GAFFELTRUCKS, ELEKTRISK - BBX50-SERIEN -6 FB25SHE-6 BBX (90001A - >/ 93001->)



DIFFERENTIALE + REDUKTIONSGEARKASSE

Kapacitet: 8 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	SP Gear 1071	

Kontroller alle 3 måneder/ 600 timer, skift alle 6 måneder/ 1200 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	SP Gear 1071	

Skift alle 1 måneder/ 200 timer

HYDRAULISK SYSTEM

Kapacitet: 33 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 32	Perlus AF 32	

Kontroller alle 8 timer, skift alle 6 måneder/ 1200 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 32	Perlus AF 32	

Skift alle 1 måneder/ 200 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,15 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Drauliquid DOT 3		

Kontroller alle 8 timer, skift alle 6 måneder/ 1200 timer

KOMATSU GAFFELTRUCKS, ELEKTRISK - BBX50-SERIEN -6 FB25SHE-6 BBX (90001A - >/ 93001->)



SMØREPUNKTER/NIPLER		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.