

KOMATSU GAFFELTRUCKS, ELEKTRISK - TUSK ABX/BSX/CBX 1200CBGH-1 CBX (500001A ->)



DIFFERENTIALE + REDUKTIONSGEARKASSE

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 3 måneder/ 600 timer, skift alle 6 måneder/ 1200 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 1 måneder/ 200 timer

HYDRAULISK SYSTEM

Kapacitet: 72 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Multifleet SCD 10W		

Kontroller alle 8 timer, skift alle 6 måneder/ 1200 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1		
Multifleet SCD 10W		

Skift alle 1 måneder/ 200 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,47 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Drauliquid DOT 3		

Kontroller alle 8 timer, skift alle 6 måneder/ 1200 timer

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or

PRODUKTANBEFALING

KOMATSU GAFFELTRUCKS, ELEKTRISK - TUSK ABX/BSX/CBX 1200CBGH-1 CBX (500001A ->)



inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.