

KOMATSU GAFFELTRUCKS, ELEKTRISKE FB FB12M-1R



REDUKTIONSGEAR

Kapacitet: 0,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 6 måneder/ 1200 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 200 timer

HYDRAULISK SYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 32

Skift alle 6 måneder/ 1200 timer

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

ATF-A

Skift alle 6 måneder/ 1200 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 32

Skift alle 200 timer

ANVEND

Første Service

KLIMA

Arktisk

PRODUKTANBEFALING 1

ATF-A

Skift alle 200 timer

KOMATSU GAFFELTRUCKS, ELEKTRISKE FB FB12M-1R



HYDRAULISK BREMSESYSTEM

Kapacitet: 0,51 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Skift alle 6 måneder/ 1200 timer

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.