

# KOMATSU GAFFELTRUCKS, ELEKTRISKE FB FB19SH-1 ASX-HP (K06053B ->)



## GEARKASSE

Kapacitet: 10 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

## HYDRAULISK SYSTEM

Kapacitet: 42 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Perlus H 32**

PRODUKTANBEFALING 2

**Perlus AF 32**

*Kontroller alle 40 timer, skift alle 12 måneder/ 2000 timer*

## HYDRAULISK BREMSESYSTEM

Kapacitet: 0,15 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Drauliquid DOT 3**

*Kontroller alle 2 måneder/ 350 timer, skift alle 12 måneder/ 2000 timer*

## SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Labora Grease**

PRODUKTANBEFALING 2

**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3

**MP Lithep Grease EP 2**

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*