

KOMATSU GAFFELTRUCKS, LP- GAS/BENZIN - BX50-SERIEN -16 FG25HTUS- 16 NISSAN K25 TIER 2 (210001A ->)



MOTOR Nissan K25
Kapacitet: 3,8 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

Kontroller alle 8 timer, skift alle 3 måneder/ 500 timer

DIFFERENTIALE
Kapacitet: 6 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 1 måneder/ 200 timer, skift alle 6 måneder/ 1200 timer

TORQFLOW-TRANSMISSION Torqflow
Kapacitet: 9,6 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 1 måneder/ 200 timer, skift alle 6 måneder/ 1200 timer

HYDRAULISK SYSTEM
Kapacitet: 55 liter (Hydrauliktank)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Perlus H 32

PRODUKTANBEFALING 2

Perlus AF 32

Kontroller alle 8 timer, skift alle 6 måneder/ 1200 timer

HYDRAULISK BREMSESYSTEM
Kapacitet: 0,15 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Kontroller alle 8 timer, skift alle 6 måneder/ 1200 timer

KOMATSU GAFFELTRUCKS, LP- GAS/BENZIN - BX50-SERIEN -16 FG25HTUS- 16 NISSAN K25 TIER 2 (210001A ->)



SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 9,1 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15+	Coolant SP 12	

Kontroller alle 8 timer, skift alle 12 måneder/ 2400 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.