

# KOMATSU GAFFELTRUCKS, LP-GAS/BENZIN FG FG30T-IE



**MOTOR** Nissan H20

ANVEND

Normal

KLIMA

Tropisk

PRODUKTANBEFALING 1

**Multifleet SCD 40**

*Skift alle 200 timer*

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

**Kroontrak MTH 10W-30**

PRODUKTANBEFALING 2

**Synfleet SHPD 10W-40**

PRODUKTANBEFALING 3

**Multifleet SHPD 10W-40**

*Skift alle 200 timer*

**MOTOR** Nissan H25

ANVEND

Normal

KLIMA

Tropisk

PRODUKTANBEFALING 1

**Multifleet SCD 40**

*Skift alle 200 timer*

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

**Kroontrak MTH 10W-30**

PRODUKTANBEFALING 2

**Synfleet SHPD 10W-40**

PRODUKTANBEFALING 3

**Multifleet SHPD 10W-40**

*Skift alle 200 timer*

# KOMATSU GAFFELTRUCKS, LP-GAS/BENZIN FG FG30T-IE



## TRANSAXSEL

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Tropisk |

|                          |  |  |
|--------------------------|--|--|
| PRODUKTANBEFALING 1      |  |  |
| <b>Multifleet SCD 40</b> |  |  |

Skift alle 6 måneder/ 1200 timer

|        |                  |
|--------|------------------|
| ANVEND | KLIMA            |
| Normal | Middelhavsagtigt |

|                             |                             |                               |
|-----------------------------|-----------------------------|-------------------------------|
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3           |
| <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> | <b>Multifleet SHPD 10W-40</b> |

Skift alle 6 måneder/ 1200 timer

|                |         |
|----------------|---------|
| ANVEND         | KLIMA   |
| Første Service | Tropisk |

|                          |  |  |
|--------------------------|--|--|
| PRODUKTANBEFALING 1      |  |  |
| <b>Multifleet SCD 40</b> |  |  |

Skift alle 200 timer

|                |                  |
|----------------|------------------|
| ANVEND         | KLIMA            |
| Første Service | Middelhavsagtigt |

|                             |                             |                               |
|-----------------------------|-----------------------------|-------------------------------|
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3           |
| <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> | <b>Multifleet SHPD 10W-40</b> |

Skift alle 200 timer

## HYDRAULISK SYSTEM

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Tropisk |

|                     |  |  |
|---------------------|--|--|
| PRODUKTANBEFALING 1 |  |  |
| <b>Perlus H 68</b>  |  |  |

Skift alle 6 måneder/ 1200 timer

|        |                  |
|--------|------------------|
| ANVEND | KLIMA            |
| Normal | Middelhavsagtigt |

|                     |  |  |
|---------------------|--|--|
| PRODUKTANBEFALING 1 |  |  |
| <b>Perlus H 46</b>  |  |  |

Skift alle 6 måneder/ 1200 timer

|        |       |
|--------|-------|
| ANVEND | KLIMA |
| Normal | Koldt |

|                     |  |  |
|---------------------|--|--|
| PRODUKTANBEFALING 1 |  |  |
| <b>Perlus H 22</b>  |  |  |

Skift alle 6 måneder/ 1200 timer

# KOMATSU GAFFELTRUCKS, LP- GAS/BENZIN FG FG30T-IE



| ANVEND              |  | KLIMA   |
|---------------------|--|---------|
| Første Service      |  | Tropisk |
| PRODUKTANBEFALING 1 |  |         |
| <b>Perlus H 68</b>  |  |         |

Skift alle 200 timer

| ANVEND              |  | KLIMA            |
|---------------------|--|------------------|
| Første Service      |  | Middelhavsagtigt |
| PRODUKTANBEFALING 1 |  |                  |
| <b>Perlus H 46</b>  |  |                  |

Skift alle 200 timer

| ANVEND              |  | KLIMA |
|---------------------|--|-------|
| Første Service      |  | Koldt |
| PRODUKTANBEFALING 1 |  |       |
| <b>Perlus H 22</b>  |  |       |

Skift alle 200 timer

## HYDRAULISK BREMSESYSTEM

| ANVEND                           |                           | KLIMA                   |
|----------------------------------|---------------------------|-------------------------|
| Normal                           |                           | Moderat                 |
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2       | PRODUKTANBEFALING 3     |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> | <b>Drauliquid DOT 3</b> |

Skift alle 6 måneder/ 1200 timer

## HEJSEKÆDER

| ANVEND              |  | KLIMA   |
|---------------------|--|---------|
| Normal              |  | Moderat |
| PRODUKTANBEFALING 1 |  |         |
| <b>HDX 30</b>       |  |         |

## HJULNAVSLEJER

| ANVEND               |                                 | KLIMA                        |
|----------------------|---------------------------------|------------------------------|
| Normal               |                                 | Moderat                      |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

# KOMATSU GAFFELTRUCKS, LP- GAS/BENZIN FG FG30T-IE



| NIPLER                                      |                                                        |                                                     |
|---------------------------------------------|--------------------------------------------------------|-----------------------------------------------------|
| ANVEND<br>Normal                            |                                                        | KLIMA<br>Moderat                                    |
| PRODUKTANBEFALING 1<br><b>Labora Grease</b> | PRODUKTANBEFALING 2<br><b>Q5 MP Calcep Grease EP 2</b> | PRODUKTANBEFALING 3<br><b>MP Lithep Grease EP 2</b> |

| RULLER                                      |                                                        |                                                     |
|---------------------------------------------|--------------------------------------------------------|-----------------------------------------------------|
| ANVEND<br>Normal                            |                                                        | KLIMA<br>Moderat                                    |
| PRODUKTANBEFALING 1<br><b>Labora Grease</b> | PRODUKTANBEFALING 2<br><b>Q5 MP Calcep Grease EP 2</b> | PRODUKTANBEFALING 3<br><b>MP Lithep Grease EP 2</b> |

**RYKKEKONTROL**

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*