KOMATSU FORKLIFT TRUCKS, LPG/PETROL - AX/BX20 SERIES -14/-17 FG20HTLS-14 NISSAN K25



ENGINE Nissan K25 Capacity: 4,25 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	Dieselfleet MSP 10W-30	
Check every 8 hours, change every 3 mod	nths/ 500 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	Dieselfleet MSP 10W-30	

DIFFERENTIAL Capacity: 5,7 liter			
use Normal		climate Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90		
Chock over 2 months/600 hours	change every 6 months / 1200 hours		

Check every 3 months/ 600 hours, change every 6 months/ 1200 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 1 months/ 200 hours

Change every 1 months/ 200 hours

TRANSMISSION POWERSHIFT Torqflow Capacity: 11,8 liter			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
ATF Dexron II-D			
Check every 3 months/ 600 hours, change every 6 months/ 1200 hours			
USE	CLIMATE		
Initial service	Moderate		
PRODUCT RECOMMENDATION 1			
ATF Dexron II-D			
Change every 1 months/ 200 hours			

KOMATSU FORKLIFT TRUCKS, LPG/PETROL - AX/BX20 SERIES -14/-17 FG20HTLS-14 NISSAN K25



HYDRAULIC SYSTEM Capacity: 56 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Perlus H 32	Perlus AF 32		
Check every 8 hours, change every 6 months/ 1200 hours			
USE		CLIMATE	
Initial service		Moderate	

PRODUCT RECOMMENDATION 2

Perlus AF 32

Change every 1 months/ 200 hours

PRODUCT RECOMMENDATION 1

Perlus H 32

HYDRAULIC BRAKE SYSTEM Capacity: 0,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

Check every 8 hours, change every 6 months/ 1200 hours

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 9,2 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Check every 8 hours, change every	12 months/2400 hours		

Check every 8 hours, change every 12 months/ 2400 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.