

KOMATSU GAFFELTRUCKS, LPG/BENZIN - AX/BX20-SERIE -14/-17 FG25ST-14 NISSAN K21



MOTOR Nissan K21
Kapacitet: 4,25 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Synfleet SHPD 10W-40

PRODUKTANBEFALING 2

Dieselfleet MSP 10W-30

Kontroller alle 8 timer, skift alle 3 måneder/ 500 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Synfleet SHPD 10W-40

PRODUKTANBEFALING 2

Dieselfleet MSP 10W-30

Skift alle 1 måneder/ 200 timer

DIFFERENTIALE

Kapacitet: 5,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 3 måneder/ 600 timer, skift alle 6 måneder/ 1200 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 1 måneder/ 200 timer

GEAR POWERSHIFT Torqflow

Kapacitet: 11,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 3 måneder/ 600 timer, skift alle 6 måneder/ 1200 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Skift alle 1 måneder/ 200 timer

KOMATSU GAFFELTRUCKS, LPG/BENZIN - AX/BX20-SERIE -14/-17 FG25ST-14 NISSAN K21



HYDRAULISK SYSTEM

Kapacitet: 36 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 32	Perlus AF 32	

Kontroller alle 8 timer, skift alle 6 måneder/ 1200 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 32	Perlus AF 32	

Skift alle 1 måneder/ 200 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Drauliquid DOT 3		

Kontroller alle 8 timer, skift alle 6 måneder/ 1200 timer

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 9,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Kontroller alle 8 timer, skift alle 12 måneder/ 2400 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.