

KOMATSU GRAVEMASKINER MED LARVEBÅND PC/HB PC07-2E (1994-1999)



MOTOR Komatsu 3D72-F2HA
Kapacitet: 3,65 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Multifleet SCD 40	Multifleet SCD 30

Skift alle 250 timer/ 6 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	
Multifleet SCD 20W-20	

Skift alle 250 timer/ 6 måneder

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1	
Multifleet SCD 10W	

Skift alle 250 timer/ 6 måneder

HYDRAULISK SYSTEM
Kapacitet: 32 liter (Hydrauliktank)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	
Multifleet SCD 10W	

Skift alle 2000 timer

KØLESYSTEM
Kapacitet: 3,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Coolant -38 Organic NF	Coolant -26

DREJEKRANS

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KOMATSU GRAVEMASKINER MED LARVEBÅND PC/HB PC07-2E (1994-1999)



KØREREDUKTIONSENHED

Kapacitet: 0,5 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 30

LED

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

TILKOBLINGSPLADE TANDSTANGSDREV

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.