

KOMATSU GRAVEMASKINER MED LARVEBÅND PC/HB PC1250LC-8 ECOT3 (2006-2014)



MOTOR Komatsu SAA6D170E-5
Kapacitet: 86 liter (Efterfyld), Kapacitet: 97 liter (Tør efterfyld)

ANVEND	KLIMA
Foretrukne	Moderat

PRODUKTANBEFALING 1		
Dieselfleet MSP 15W-40		

Kontroller alle 8 timer, skift alle 12 måneder

ANVEND	KLIMA
Alternativ (acceptabel)	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Kontroller alle 8 timer, skift alle 12 måneder

KRAFTOVERFØRING

Kapacitet: 13,5 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Gear Oil Alcat 30		

Skift alle 1000 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1		
Gear Oil Alcat 10W		

Skift alle 1000 timer

HYDRAULISK SYSTEM

Kapacitet: 670 liter (Efterfyld), Kapacitet: 1180 liter (System)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 10W	Perlus H 46	

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Q11 Xtreme Duty Grease EP 2		

KOMATSU GRAVEMASKINER MED LARVEBÅND PC/HB PC1250LC-8 ECOT3 (2006-2014)



KØLESYSTEM

Kapacitet: 142 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Skift alle 24 måneder/ 4000 timer

KØREREDUKTIONSENHED

Kapacitet: 22 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 30

Skift alle 2000 timer

SVINGREDUKTIONSENHED

Kapacitet: 24,3 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gear Oil Alcat 30

Skift alle 1000 timer

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

Skift alle 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.