

KOMATSU GRAVEMASKINER MED LARVEBÅND PC/HB PC130-6 (1999-2004)



MOTOR Komatsu S4D102E-1

Kapacitet: 17,5 liter, Kapacitet: 17 liter (Efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Dieselfleet MSP 15W-40

Kontroller alle 8 timer, skift alle 250 timer

KRAFTOVERFØRING

Kapacitet: 0,75 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 30

Kontroller alle 2000 timer

HYDRAULISK SYSTEM

Kapacitet: 90 liter (Efterfyld), Kapacitet: 100 liter (Hydrauliktank), Kapacitet: 140 liter (System)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Dieselfleet MSP 15W-40

PRODUKTANBEFALING 2

Gear Oil Alcat 10W

PRODUKTANBEFALING 3

Perlus H 46

Kontroller alle 8 timer, skift alle 5000 timer

ANVEND	KLIMA
50% anvendelse af afbryder	Moderat

PRODUKTANBEFALING 1

Dieselfleet MSP 15W-40

PRODUKTANBEFALING 2

Gear Oil Alcat 10W

PRODUKTANBEFALING 3

Perlus H 46

Kontroller alle 8 timer, skift alle 1500 timer

ANVEND	KLIMA
100% anvendelse af afbryder	Moderat

PRODUKTANBEFALING 1

Dieselfleet MSP 15W-40

PRODUKTANBEFALING 2

Gear Oil Alcat 10W

PRODUKTANBEFALING 3

Perlus H 46

Kontroller alle 8 timer, skift alle 1000 timer

KOMATSU GRAVEMASKINER MED LARVEBÅND PC/HB PC130-6 (1999-2004)



SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 100 timer

KØLESYSTEM

Kapacitet: 18,2 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15+	Coolant SP 12	

Kontroller alle 8 timer, skift alle 24 måneder/ 4000 timer

KØREREDUKTIONSENHED

Kapacitet: 2,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gear Oil Alcat 30		

Kontroller alle 250 timer, skift alle 1000 timer

SVINGREDUKTIONSENHED

Kapacitet: 2,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gear Oil Alcat 30		

Kontroller alle 100 timer, skift alle 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.