

# KOMATSU GRAVEMASKINER MED LARVEBÅND PC/HB PC14R-2 KOMATSU 3D67E-1A (F00003 ->) (2005-2008)



**MOTOR** Komatsu 3D67E-1  
Kapacitet: 3,3 liter (Servicepåfyldning), Kapacitet: 3,6 liter (Tør efterfyld)

| ANVEND                                  | KLIMA            |
|-----------------------------------------|------------------|
| Normalt, svovlniveau i brændstof <0,5 % | Middelhavsagtigt |

PRODUKTANBEFALING 1

**Multifleet SCD 30**

*Skift alle 500 timer*

| ANVEND                                  | KLIMA   |
|-----------------------------------------|---------|
| Normalt, svovlniveau i brændstof <0,5 % | Moderat |

PRODUKTANBEFALING 1

**Kroontrak MTH 10W-30**

PRODUKTANBEFALING 2

**Synfleet SHPD 10W-40**

PRODUKTANBEFALING 3

**Dieselfleet CD+ 15W-40**

*Skift alle 500 timer*

| ANVEND                                  | KLIMA |
|-----------------------------------------|-------|
| Normalt, svovlniveau i brændstof <0,5 % | Koldt |

PRODUKTANBEFALING 1

**Multifleet SCD 10W**

*Skift alle 500 timer*

**HYDRAULISK SYSTEM**  
Kapacitet: 15,2 liter (Servicepåfyldning), Kapacitet: 23,8 liter (Tør efterfyld)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Kroontrak MTH 10W-30**

PRODUKTANBEFALING 2

**Synfleet SHPD 10W-40**

PRODUKTANBEFALING 3

**Dieselfleet CD+ 15W-40**

*Kontroller alle 8 timer, skift alle 12 måneder/ 2000 timer*

| ANVEND                     | KLIMA   |
|----------------------------|---------|
| Biologisk nedbrydelig olie | Moderat |

PRODUKTANBEFALING 1

**Perlus Biosynth 46**

*Kontroller alle 8 timer, skift alle 12 måneder/ 2000 timer*

| ANVEND                              | KLIMA   |
|-------------------------------------|---------|
| Første service, bionedbrydelig olie | Moderat |

PRODUKTANBEFALING 1

**Perlus Biosynth 46**

*Skift alle 500 timer*

# KOMATSU GRAVEMASKINER MED LARVEBÅND PC/HB PC14R-2 KOMATSU 3D67E-1A (F00003 ->) (2005-2008)



## SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**MoS2 Grease EP 2**

## KØLESYSTEM

Kapacitet: 3,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Coolant SP 15+**

PRODUKTANBEFALING 2

**Coolant SP 12**

*Kontroller alle 8 timer, skift alle 24 måneder/ 2000 timer*

## KØREREDUKTIONSENHED

Kapacitet: 0,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Gear Oil Alcat 30**

*Skift alle 1000 timer*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*