

KOMATSU GRAVEMASKINER MED LARVEBÅND PC/HB PC210LC-7K K40001-> (2002-2005)



MOTOR Komatsu SAA6D102E-2
Kapacitet: 24 liter (Servicepåfyldning), Kapacitet: 26,3 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Multifleet SCD 30		

Skift alle 250 timer/ 6 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Skift alle 250 timer/ 6 måneder

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1		
Multifleet SCD 10W		

Skift alle 250 timer/ 6 måneder

SLUTDREV
Kapacitet: 4,5-4,7 liter

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1		
Gear Oil Alcat 30		

Skift alle 250 timer/ 6 måneder

ANVEND	KLIMA
Efterfølgende	Moderat

PRODUKTANBEFALING 1		
Gear Oil Alcat 30		

Skift alle 1000 timer

KOMATSU GRAVEMASKINER MED LARVEBÅND PC/HB PC210LC-7K K40001-> (2002-2005)



HYDRAULISK SYSTEM

Kapacitet: 166 liter (Servicepåfyldning), Kapacitet: 239 liter (Tør efterfyld)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Skift alle 2000 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Skift alle 250 timer/ 6 måneder

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 22,9 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

DÆMPERHUS

Kapacitet: 0,75 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gear Oil Alcat 30		

Skift alle 2000 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1		
Gear Oil Alcat 30		

Skift alle 250 timer/ 6 måneder

KOMATSU GRAVEMASKINER MED LARVEBÅND PC/HB PC210LC-7K K40001-> (2002-2005)

**SVINGREDUKTIONSENHED**

Kapacitet: 6,6 liter

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 30*Skift alle 250 timer/ 6 måneder*

ANVEND

Efterfølgende

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 30*Skift alle 1000 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.