

KOMATSU GRAVEMASKINER MED LARVEBÅND PC/HB PC228US-3 30001-> (2001-2010)



MOTOR Komatsu SAA6D107E-1
Kapacitet: 24 liter (Servicepåfyldning), Kapacitet: 26,3 liter (Tør efterfyld)

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 250 timer/ 6 måneder

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Dieselfleet CD+ 15W-40

Skift alle 250 timer/ 6 måneder

ANVEND
Normal

KLIMA
Koldt

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 250 timer/ 6 måneder

SLUTDREV

Kapacitet: 5,2-5,4 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30

HYDRAULISK SYSTEM

Kapacitet: 126 liter (Servicepåfyldning), Kapacitet: 185 liter (Tør efterfyld)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Dieselfleet CD+ 15W-40

Skift alle 2000 timer

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KOMATSU GRAVEMASKINER MED LARVEBÅND PC/HB PC228US-3 30001-> (2001-2010)



KØLESYSTEM

Kapacitet: 21,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

BÆRERULLER

Kapacitet: 0,08 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30

DÆMPERHUS

Kapacitet: 0,75 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 2000 timer

LARVEBÅNDSRULLER

Kapacitet: 0,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30

SPOR MELLEMLJUL

Kapacitet: 0,07 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30

KOMATSU GRAVEMASKINER MED LARVEBÅND PC/HB PC228US-3 30001-> (2001-2010)



SVINGREDUKTIONSENHED

Kapacitet: 6,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.