

KOMATSU GRAVEMASKINER MED LARVEBÅND PC/HB PC240-10 KOMATSU SAA6D107E-2 TIER 4I / EU-STAGE IIIB (2012-



MOTOR Komatsu SAA6D107E-2

Kapacitet: 23,1 liter (Olieskiftskapacitet), Kapacitet: 25,4 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Dieselfleet MSP 10W-30

PRODUKTANBEFALING 2

Dieselfleet MSP 15W-40

Kontroller alle 10 timer, skift alle 500 timer

ANVEND

Koldt klima

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra FE 5W-30

PRODUKTANBEFALING 2

Armado Synth LSP Ultra 5W-30

PRODUKTANBEFALING 3

Armado Synth MSP 5W-40

Kontroller alle 10 timer, skift alle 250 timer

HYDRAULISK SYSTEM

Kapacitet: 132 liter (Olieskiftskapacitet), Kapacitet: 234 liter (Total)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

PRODUKTANBEFALING 2

Perlus H 46

Kontroller alle 10 timer, skift alle 5000 timer

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q11 Xtreme Duty Grease EP 2

PRODUKTANBEFALING 3

Q5 MP Calcep Grease EP 2

Kontroller alle 100 timer

KØLESYSTEM

Kapacitet: 36 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Kontroller alle 10 timer, skift alle 24 måneder/ 4000 timer

KOMATSU GRAVEMASKINER MED LARVEBÅND PC/HB PC240-10 KOMATSU SAA6D107E-2 TIER 4I / EU-STAGE IIIB (2012-



DAMPKAPASITEIT

Kapacitet: 0,65 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gear Oil Alcat 30		

Kontroller alle 1000 timer

KØREREDUKTIONSENHED

Kapacitet: 5 liter (hver side, servicepåfyldning), Kapacitet: 5,4 liter (hver side, tør påfyldning)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gear Oil Alcat 30		

Kontroller alle 500 timer, skift alle 2000 timer

SVINGREDUKTIONSENHED

Kapacitet: 6,5 liter (Olieskiftskapacitet), Kapacitet: 7,1 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gear Oil Alcat 30		

Kontroller alle 500 timer, skift alle 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.