

KOMATSU GRAVEMASKINER MED LARVEBÅND PC/HB PC270-7 (2002-2007)



MOTOR Komatsu SAA6D102E-2
Kapacitet: 26,3 liter, Kapacitet: 24 liter (Efterfyld)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Dieselfleet MSP 15W-40

Kontroller alle 8 timer, skift alle 500 timer

HYDRAULISK SYSTEM

Kapacitet: 247 liter, Kapacitet: 143 liter (Efterfyld)

ANVEND
Foretrukne

KLIMA
Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

PRODUKTANBEFALING 2

Perlus H 46

Kontroller alle 8 timer, skift alle 5000 timer

ANVEND

Alternativ (acceptabel)

KLIMA
Moderat

PRODUKTANBEFALING 1

Dieselfleet MSP 15W-40

Kontroller alle 8 timer, skift alle 5000 timer

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q11 Xtreme Duty Grease EP 2

PRODUKTANBEFALING 3

Q5 MP Calcep Grease EP 2

Skift alle 100 timer

KØLESYSTEM

Kapacitet: 30,9 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Kontroller alle 8 timer, skift alle 24 måneder/ 4000 timer

KOMATSU GRAVEMASKINER MED LARVEBÅND PC/HB PC270-7 (2002-2007)



DÆMPERHUS

Kapacitet: 0,75 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 30

Skift alle 1000 timer

KØREREDUKTIONSENHED

Kapacitet: 4,7 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 30

Kontroller alle 500 timer, skift alle 2000 timer

SVING TANDSTANGSDREV

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q11 Xtreme Duty Grease EP 2

PRODUKTANBEFALING 3

Q5 MP Calcep Grease EP 2

Skift alle 500 timer

SVINGREDUKTIONSENHED

Kapacitet: 6,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 30

Kontroller alle 500 timer, skift alle 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.