

KOMATSU GRAVEMASKINER MED LARVEBÅND PC/HB PC350LC-8 (2007-2013)



MOTOR Komatsu SAA6D114E-3
Kapacitet: 35 liter (Servicepåfyldning), Kapacitet: 40 liter (Tør efterfyld)

ANVEND	KLIMA
Normal (alternativ)	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra FE 5W-30	Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40

Skift alle 500 timer

ANVEND	KLIMA
Normal (foretrukne)	Moderat

PRODUKTANBEFALING 1		
Dieselfleet MSP 15W-40		

Skift alle 12 måneder

ANVEND	KLIMA
Acceptabel	Middelhavsagtigt

PRODUKTANBEFALING 1		
Multifleet SCD 30		

Skift alle 250 timer/ 6 måneder

ANVEND	KLIMA
Acceptabel	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40

Skift alle 250 timer/ 6 måneder

SLUTDREV
Kapacitet: 9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gear Oil Alcat 30		

Skift alle 2000 timer

HYDRAULISK SYSTEM
Kapacitet: 188 liter (Servicepåfyldning), Kapacitet: 365 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 10W	Perlus H 46	

Skift alle 5000 timer

KOMATSU GRAVEMASKINER MED LARVEBÅND PC/HB PC350LC-8 (2007-2013)



SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 32 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15+	Coolant SP 12	

DÆMPERHUS

Kapacitet: 1,3 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gear Oil Alcat 30		

Skift alle 1000 timer

SVINGREDUKTIONSENHED

Kapacitet: 16,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gear Oil Alcat 30		

Skift alle 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.