

KOMATSU GRAVEMASKINER MED LARVEBÅND PC/HB PC45MR-3 5457-> (2008- 2018)



MOTOR Komatsu 4D88E-6

Kapacitet: 7,5 liter (Olieskiiftskapacitet), Kapacitet: 8,1 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Dieselfleet MSP 15W-40

HYDRAULISK SYSTEM

Kapacitet: 20 liter (Olieskiiftskapacitet), Kapacitet: 55 liter (Total)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

PRODUKTANBEFALING 2

Perlus H 46

ANVEND

Biologisk nedbrydelig olie

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus Biosynth 46

SMØREPUNKTER/NIPLER

ANVEND

Foretrukne

KLIMA

Moderat

PRODUKTANBEFALING 1

Q11 Xtreme Duty Grease EP 2

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 8,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

KOMATSU GRAVEMASKINER MED LARVEBÅND PC/HB PC45MR-3 5457-> (2008- 2018)



KØREREDUKTIONSENHED

Kapacitet: 0,8 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Oil Alcat 30

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.