

KOMATSU GRAVEMASKINER MED LARVEBÅND PC/HB PC50MR-2 5001 -> (2004-2010)



MOTOR Komatsu 4D88E-5
Kapacitet: 7,4 liter (Servicepåfyldning), Kapacitet: 8 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Multifleet SCD 30		

Kontroller alle 10 timer, skift alle 500 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Kontroller alle 10 timer, skift alle 500 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1		
Multifleet SCD 10W		

Kontroller alle 10 timer, skift alle 500 timer

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1		
Multifleet SCD 30		

Kontroller alle 10 timer, skift alle 250 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Kontroller alle 10 timer, skift alle 250 timer

ANVEND	KLIMA
Første Service	Koldt

PRODUKTANBEFALING 1		
Multifleet SCD 10W		

Kontroller alle 10 timer, skift alle 250 timer

KOMATSU GRAVEMASKINER MED LARVEBÅND PC/HB PC50MR-2 5001 -> (2004-2010)

**SLUTDREV**

Kapacitet: 0,8 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30*Kontroller alle 100 timer, skift alle 1000 timer***HYDRAULISK SYSTEM**

Kapacitet: 55 liter (Komplet), Kapacitet: 20 liter (Olieskiftskapacitet)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Dieselfleet CD+ 15W-40*Kontroller alle 10 timer, skift alle 2000 timer*

ANVEND

Biologisk nedbrydelig olie

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus Biosynth 46*Kontroller alle 10 timer, skift alle 2000 timer***SMØREPUNKTER/NIPLER**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Q11 Xtreme Duty Grease EP 2**KØLESYSTEM**

Kapacitet: 7,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26*Kontroller alle 10 timer, skift alle 2000 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.