

KOMATSU GRAVEMASKINER MED LARVEBÅND PC/HB PC600-8R (2009-2014)



MOTOR Komatsu SAA6D140

Kapacitet: 45 liter, Kapacitet: 40 liter (Efterfyld)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Dieselfleet CD+ 15W-40

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1

Multifleet SCD 10W

KRAFTOVERFØRING

Kapacitet: 7,2 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Gear Oil Alcat 30

Skift alle 1000 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1

Gear Oil Alcat 10W

Skift alle 1000 timer

HYDRAULISK SYSTEM

Kapacitet: 520 liter, Kapacitet: 360 liter (Efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Dieselfleet CD+ 15W-40

Skift alle 5000 timer

KOMATSU GRAVEMASKINER MED LARVEBÅND PC/HB PC600-8R (2009-2014)



SMØREPUNKTER/NIPLER		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

KØLESYSTEM Kapacitet: 58 liter		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Coolant SP 15+	PRODUKTANBEFALING 2 Coolant SP 12	

KØREREDUKTIONSENHED Kapacitet: 10,5 liter		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Gear Oil Alcat 30		

Skift alle 2000 timer

SVINGREDUKTIONSENHED Kapacitet: 13 liter		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Gear Oil Alcat 30		

Skift alle 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.