

KOMATSU LÆSSERE, SKID-STEER CK/SK

SK815-5 KOMATSU 4D88E-5KFD

(37BF00006->) (2001 OG EFTER)



MOTOR Komatsu 4D88E-5
Kapacitet: 8 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 40	Multifleet SCD 30	

Skift alle 250 timer/ 6 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40

Skift alle 250 timer/ 6 måneder

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1		
Multifleet SCD 10W		

Skift alle 250 timer/ 6 måneder

GEAR HYDROSTATISK

Kapacitet: 27 liter (Efterfyld), Kapacitet: 38 liter (Total)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Multifleet SCD 10W		

GEAR SLUT

Kapacitet: 15,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40

KOMATSU LÆSSERE, SKID-STEER CK/SK SK815-5 KOMATSU 4D88E-5KFD (37BF00006->) (2001 OG EFTER)



HYDRAULISK SYSTEM

Kapacitet: 27 liter (Efterfyld), Kapacitet: 38 liter (Total)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 2000 timer

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.