

KOMATSU MOBILE KNUSERE BR BR550JG-1 KOMATSU SAA6D125E-2



MOTOR Komatsu SA6D125E-2

Kapacitet: 34 liter (Servicepåfyldning), Kapacitet: 38 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 250 timer/ 6 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Dieselfleet CD+ 15W-40

Skift alle 250 timer/ 6 måneder

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 250 timer/ 6 måneder

HYDRAULISK SYSTEM

Kapacitet: 270 liter (Servicepåfyldning), Kapacitet: 370 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Dieselfleet CD+ 15W-40

Skift alle 5000 timer

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 43,9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

KOMATSU MOBILE KNUSERE BR BR550JG-1 KOMATSU SAA6D125E-2



DÆMPERHUS

Kapacitet: 0,75 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 1000 timer

GRIZZLY-FØDER VIBRATORHUS

Kapacitet: 15 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 1000 timer

KÆBEKNUSERMOTOR LEJEHUS

Kapacitet: 8,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 1000 timer

TRANSPORTBÅNDSMOTOR MASKINHUS

Kapacitet: 2,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.