

# KOMATSU SPOREDE SKOVANHÆNGERE LW/WH WH613 (2004-2009)



**MOTOR** Komatsu 4D104E-1  
Kapacitet: 12,8 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Agridiesel MSP 15W-40**

PRODUKTANBEFALING 2

**Agridiesel CRD+ 15W-40**

PRODUKTANBEFALING 3

**Armado Synth 5W-30**

*Kontroller alle 8 timer, skift alle 6 måneder/ 500 timer*

## DIFFERENTIALE BAG

Kapacitet: 7,1 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Kroontrak CVT 10W-40**

PRODUKTANBEFALING 2

**Agrifluid Synth XHP Ultra**

PRODUKTANBEFALING 3

**Agrifluid HT-Plus**

*Kontroller alle 3 måneder/ 250 timer, skift alle 12 måneder/ 1000 timer*

## DIFFERENTIALE FOR

Kapacitet: 7,1 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Kroontrak CVT 10W-40**

PRODUKTANBEFALING 2

**Agrifluid Synth XHP Ultra**

PRODUKTANBEFALING 3

**Agrifluid HT-Plus**

*Kontroller alle 3 måneder/ 250 timer, skift alle 12 måneder/ 1000 timer*

## GEAR

Kapacitet: 11,7 liter (Efterfyld), Kapacitet: 13,5 liter (Tør efterfyld)

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**ATF Dexron II-D**

*Kontroller alle 3 måneder/ 250 timer, skift alle 12 måneder/ 1000 timer*

## NAVREDUKTIONER BAG

Kapacitet: 0,7 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Kroontrak CVT 10W-40**

PRODUKTANBEFALING 2

**Agrifluid Synth XHP Ultra**

PRODUKTANBEFALING 3

**Agrifluid HT-Plus**

*Kontroller alle 3 måneder/ 250 timer, skift alle 12 måneder/ 1000 timer*

# KOMATSU SPOREDE SKOVANHÆNGERE LW/WH WH613 (2004-2009)



## NAVREDUKTIONER FOR

Kapacitet: 0,7 liter

| ANVEND                      |                                  | KLIMA                    |
|-----------------------------|----------------------------------|--------------------------|
| Normal                      |                                  | Moderat                  |
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2              | PRODUKTANBEFALING 3      |
| <b>Kroontrak CVT 10W-40</b> | <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> |

Kontroller alle 3 måneder/ 250 timer, skift alle 12 måneder/ 1000 timer

## HYDRAULISK SYSTEM

Kapacitet: 95 liter (Efterfyld), Kapacitet: 107 liter (Hydrauliktank), Kapacitet: 117 liter (System)

| ANVEND                      |                             | KLIMA                         |
|-----------------------------|-----------------------------|-------------------------------|
| Normal                      |                             | Moderat                       |
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3           |
| <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

Kontroller alle 6 måneder/ 500 timer, skift alle 12 måneder/ 1000 timer

| ANVEND                    |  | KLIMA   |
|---------------------------|--|---------|
| Alternativ (acceptabel)   |  | Moderat |
| PRODUKTANBEFALING 1       |  |         |
| <b>Perlus Biosynth 46</b> |  |         |

Kontroller alle 6 måneder/ 500 timer, skift alle 12 måneder/ 1000 timer

| ANVEND                    |  | KLIMA   |
|---------------------------|--|---------|
| Startservice (alternativ) |  | Moderat |
| PRODUKTANBEFALING 1       |  |         |
| <b>Perlus Biosynth 46</b> |  |         |

Skift alle 500 timer

## HYDRAULISK BREMSESYSTEM

Kapacitet: 0,65 liter

| ANVEND                 |  | KLIMA   |
|------------------------|--|---------|
| Normal                 |  | Moderat |
| PRODUKTANBEFALING 1    |  |         |
| <b>ATF Dexron II-D</b> |  |         |

Kontroller alle 8 timer, skift alle 24 måneder/ 2000 timer

# KOMATSU SPOREDE SKOVANHÆNGERE LW/WH WH613 (2004-2009)



## KØLESYSTEM

Kapacitet: 20 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

### PRODUKTANBEFALING 2

**Coolant -26**

*Kontroller alle 8 timer, skift alle 24 måneder/ 2000 timer*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*