

KRAMER GUMMIHJULSLÆSSERE 180 340-01 0001 -> - YANMAR 3TNV88



MOTOR Yanmar 3TNV88
Kapacitet: 7,2 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Multifleet SCD 30		

Kontroller alle 10 timer, skift alle 500 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak CVT 10W-40	Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40

Kontroller alle 10 timer, skift alle 500 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1		
Multifleet SCD 10W		

Kontroller alle 10 timer, skift alle 500 timer

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1		
Multifleet SCD 30		

Skift alle 100 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak CVT 10W-40	Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40

Skift alle 100 timer

ANVEND	KLIMA
Første Service	Arktisk

PRODUKTANBEFALING 1		
Multifleet SCD 10W		

Skift alle 100 timer

KRAMER GUMMIHJULSLÆSSERE 180 340-01 0001 -> - YANMAR 3TNV88



BAGAKSEL TRANSFERGEARKASSE

Kapacitet: 0,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 500 timer, skift alle 12 måneder/ 1500 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Skift alle 100 timer

DIFFERENTIALE FOR OG BAG

Kapacitet: 2,5 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 500 timer, skift alle 12 måneder/ 1500 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Skift alle 100 timer

PLANETGEAR FOR OG BAG

Kapacitet: 0,6 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 500 timer, skift alle 12 måneder/ 1500 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Skift alle 100 timer

KRAMER GUMMIHJULSLÆSSERE 180 340-01 0001 -> - YANMAR 3TNV88



HYDRAULISK SYSTEM

Kapacitet: 40 liter (Hydrauliktank)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Perlus HCD 46		

Kontroller alle 10 timer, skift alle 12 måneder/ 1500 timer

ANVEND		KLIMA
Alternativ (acceptabel)		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Kontroller alle 10 timer, skift alle 12 måneder/ 1500 timer

ANVEND		KLIMA
Alternativ (acceptabel)		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40	

Kontroller alle 10 timer, skift alle 12 måneder/ 1500 timer

ANVEND		KLIMA
Biologisk nedbrydelig olie		Moderat
PRODUKTANBEFALING 1		
Perlus Biosynth 46		

Kontroller alle 10 timer, skift alle 12 måneder/ 1500 timer

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 50 timer

KØLESYSTEM

Kapacitet: 4,2 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

KRAMER GUMMIHJULSLÆSSERE 180 340-01 0001 -> - YANMAR 3TNV88



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.