

KUBOTA GRAVEMASKINER MED LARVEBÅND K/KH/KX/U KX015-4 KUBOTA D782-E-BH (S/N <- 63627) (2011-2018)



MOTOR Kubota D782-E
Kapacitet: 2,6 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet LSP Ultra 10W-30

Kontroller alle 10 timer, skift alle 500 timer

HYDRAULISK SYSTEM

Kapacitet: 15,5 liter (Hydrauliktank), Kapacitet: 28 liter (Total)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Perlus H 46		

Kontroller alle 10 timer, skift alle 1000 timer

ANVEND		KLIMA
Brug af afbryder <40 %		Moderat
PRODUKTANBEFALING 1		
Perlus H 46		

Kontroller alle 10 timer, skift alle 800 timer

ANVEND		KLIMA
Brug af afbryder 40-60 %		Moderat
PRODUKTANBEFALING 1		
Perlus H 46		

Kontroller alle 10 timer, skift alle 400 timer

ANVEND		KLIMA
Brug af afbryder 60-80 %		Moderat
PRODUKTANBEFALING 1		
Perlus H 46		

Kontroller alle 10 timer, skift alle 300 timer

ANVEND		KLIMA
Brug af afbryder >80 %		Moderat
PRODUKTANBEFALING 1		
Perlus H 46		

Kontroller alle 10 timer, skift alle 200 timer

KUBOTA GRAVEMASKINER MED LARVEBÅND K/KH/KX/U KX015-4 KUBOTA D782-E-BH (S/N <- 63627) (2011-2018)

**KØLESYSTEM**

Kapacitet: 2,7-2,9 liter, Kapacitet: 0,56 liter (Reservetank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26*Kontroller alle 10 timer, skift alle 24 måneder***KØREREDUKTIONSENHED**

Kapacitet: 0,33 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

Gearlube GL-4 80W*Skift alle 500 timer*

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

Gearlube GL-4 80W*Skift alle 50 timer***LARVEBÅNDSRULLER**

Kapacitet: 0,04 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30*Skift alle 2000 timer***RULLER FOR**

Kapacitet: 0,03 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30*Skift alle 2000 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.