

KUBOTA GRAVEMASKINER MED LARVEBÅND K/KH/KX/U KX057-4 KUBOTA V2607-DI-E3-BH (2009 OG EFTER)



MOTOR Kubota V2607-DI-E3B
Kapacitet: 9 liter

ANVEND	KLIMA
Normalt, svovlniveau i brændstof <0,1 %	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SCD 30

Skift alle 500 timer

ANVEND	KLIMA
Normalt, svovlniveau i brændstof <0,1 %	Koldt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 20W-20	Multifleet SCD 10W	

Skift alle 500 timer

HYDRAULISK SYSTEM

Kapacitet: 45 liter (Hydrauliktank), Kapacitet: 79 liter (Total)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Perlus H 46	Perlus H 68	Perlus AF 46

Skift alle 1000 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 32	Perlus AF 32	

Skift alle 1000 timer

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KUBOTA GRAVEMASKINER MED LARVEBÅND K/KH/KX/U KX057-4 KUBOTA V2607-DI-E3-BH (2009 OG EFTER)

**KØLESYSTEM**

Kapacitet: 8,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 11*Skift alle 24 måneder***KØREREDUKTIONSENHED**

Kapacitet: 0,9 liter (hvert)

ANVEND

Normal

KLIMA

Tropisk

PRODUKTANBEFALING 1

Gearlube HS GL-5 80W-140

PRODUKTANBEFALING 2

Gearlube GL-5 85W-140

PRODUKTANBEFALING 3

Unigear LS GL-3/GL-5 85W-140*Skift alle 500 timer*

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Skift alle 500 timer*

ANVEND

Første Service

KLIMA

Tropisk

PRODUKTANBEFALING 1

Gearlube HS GL-5 80W-140

PRODUKTANBEFALING 2

Gearlube GL-5 85W-140

PRODUKTANBEFALING 3

Unigear LS GL-3/GL-5 85W-140*Skift alle 50 timer*

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Skift alle 50 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.