

KUBOTA GRAVEMASKINER MED LARVEBÅND K/KH/KX/U KX080-4 KUBOTA V3307-CR-TE4 (T4F) (2013 OG EFTER)



MOTOR Kubota V3307-CR-TE4
Kapacitet: 9,7 liter

ANVEND	KLIMA
Normalt, svovlniveau i brændstof <15 ppm	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth MSP 10W-40	Agridiesel MSP 15W-40	Dieselfleet LSP Ultra 10W-30

Kontroller alle 10 timer, skift alle 500 timer

HYDRAULISK SYSTEM

Kapacitet: 159 liter (2-delt bom specifikation), Kapacitet: 75 liter (Hydrauliktank), Kapacitet: 146 liter (Total)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Perlus H 46		

Kontroller alle 10 timer, skift alle 1000 timer

ANVEND	KLIMA
Biologisk nedbrydelig olie	Moderat

PRODUKTANBEFALING 1		
Perlus Biosynth 46		

Kontroller alle 10 timer, skift alle 1000 timer

ANVEND	KLIMA
Brug af afbryder <40 %	Moderat

PRODUKTANBEFALING 1		
Perlus H 46		

Kontroller alle 10 timer, skift alle 800 timer

ANVEND	KLIMA
Brug af afbryder 40-60 %	Moderat

PRODUKTANBEFALING 1		
Perlus H 46		

Kontroller alle 10 timer, skift alle 400 timer

ANVEND	KLIMA
Brug af afbryder 60-80 %	Moderat

PRODUKTANBEFALING 1		
Perlus H 46		

Kontroller alle 10 timer, skift alle 300 timer

KUBOTA GRAVEMASKINER MED LARVEBÅND K/KH/KX/U KX080-4 KUBOTA V3307-CR-TE4 (T4F) (2013 OG EFTER)



ANVEND		KLIMA
Brug af afbryder >80 %		Moderat
PRODUKTANBEFALING 1		
Perlus H 46		
<i>Kontroller alle 10 timer, skift alle 200 timer</i>		

SMØREPUNKTER/NIPLER		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM		
Kapacitet: 10,5 liter, Kapacitet: 1,3 liter (Reservetank)		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	
<i>Kontroller alle 10 timer, skift alle 24 måneder</i>		

BÆRERULLER		
Kapacitet: 0,8 liter (hvert)		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Multifleet SCD 30		
<i>Skift alle 2000 timer</i>		



KUBOTA GRAVEMASKINER MED LARVEBÅND K/KH/KX/U KX080-4 KUBOTA V3307-CR-TE4 (T4F) (2013 OG EFTER)



KØREREDUKTIONSENHED

Kapacitet: 1,3 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 10 timer, skift alle 500 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 50 timer

LARVEBÅNDSRULLER

Kapacitet: 0,8 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 2000 timer

RULLER FOR

Kapacitet: 0,08 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.