

KUBOTA GRAVEMASKINER MED LARVEBÅND K/KH/KX/U KX71-2 KUBOTA V1505-EB (1997-2004)



MOTOR Kubota V1505

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2

Multifleet SHPD 15W-40

PRODUKTANBEFALING 3

Multifleet SCD 50

Kontroller alle 8 timer, skift alle 250 timer

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Multifleet SCD 20W-20

PRODUKTANBEFALING 2

Multifleet SCD 10W

Kontroller alle 8 timer, skift alle 250 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2

Multifleet SHPD 15W-40

PRODUKTANBEFALING 3

Multifleet SCD 50

Skift alle 50 timer

ANVEND

Første Service

KLIMA

Koldt

PRODUKTANBEFALING 1

Multifleet SCD 20W-20

PRODUKTANBEFALING 2

Multifleet SCD 10W

Skift alle 50 timer

KUBOTA GRAVEMASKINER MED LARVEBÅND K/KH/KX/U KX71-2 KUBOTA V1505-EB (1997-2004)



HYDRAULISK SYSTEM

Kapacitet: 87 liter (Hydrauliktank)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Perlus H 68		

Kontroller alle 10 timer, skift alle 1000 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Perlus H 46		

Kontroller alle 10 timer, skift alle 1000 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1		
Perlus H 32		

Kontroller alle 10 timer, skift alle 1000 timer

KØLESYSTEM

Kapacitet: 4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Kontroller alle 10 timer, skift alle 24 måneder

BOLTE + BØSNINGER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Kontroller alle 8 timer

KUBOTA GRAVEMASKINER MED LARVEBÅND K/KH/KX/U KX71-2 KUBOTA V1505-EB (1997-2004)



KØREREDUKTIONSENHED

Kapacitet: 0,65-1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 500 timer/ 12 måneder

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 100 timer

SPORRULLER + FORMELLEMHJUL

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 1000 timer

SVINGREDUKTIONSENHED

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.