

KUBOTA GRAVEMASKINER MED LARVEBÅND K/KH/KX/U KX91-3S2 KUBOTA D1703-M-E3-BH (TIER 4I) (2007-2011)



MOTOR Kubota D1703-M-E3B
Kapacitet: 5,9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	

Skift alle 250 timer/ 6 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	

Skift alle 50 timer

HYDRAULISK SYSTEM

Kapacitet: 36 liter (Hydrauliktank), Kapacitet: 55 liter (System)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Perlus H 46	Perlus H 68	Perlus AF 46

Kontroller alle 10 timer, skift alle 1000 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 32	Perlus AF 32	

Kontroller alle 10 timer, skift alle 1000 timer

ANVEND	KLIMA
Brug af afbryder 40-60 %	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Perlus H 46	Perlus H 68	Perlus AF 46

Kontroller alle 10 timer, skift alle 400 timer

ANVEND	KLIMA
Brug af afbryder 40-60 %	Koldt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 32	Perlus AF 32	

Kontroller alle 10 timer, skift alle 400 timer

KUBOTA GRAVEMASKINER MED LARVEBÅND K/KH/KX/U KX91-3S2 KUBOTA D1703-M-E3-BH (TIER 4I) (2007-2011)



ANVEND	KLIMA	
Brug af afbryder 60-80 %	Moderat	

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Perlus H 46	Perlus H 68	Perlus AF 46

Kontroller alle 10 timer, skift alle 300 timer

ANVEND	KLIMA	
Brug af afbryder 60-80 %	Koldt	

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 32	Perlus AF 32	

Kontroller alle 10 timer, skift alle 300 timer

ANVEND	KLIMA	
Brug af afbryder >80 %	Moderat	

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Perlus H 46	Perlus H 68	Perlus AF 46

Kontroller alle 10 timer, skift alle 200 timer

ANVEND	KLIMA	
Brug af afbryder >80 %	Koldt	

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 32	Perlus AF 32	

Kontroller alle 10 timer, skift alle 200 timer

ANVEND	KLIMA	
Brug af afbryder 20-40 %	Moderat	

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Perlus H 46	Perlus H 68	Perlus AF 46

Kontroller alle 10 timer, skift alle 800 timer

ANVEND	KLIMA	
Brug af afbryder 20-40 %	Koldt	

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 32	Perlus AF 32	

Kontroller alle 10 timer, skift alle 800 timer

SMØREPUNKTER/NIPLER

ANVEND	KLIMA	
Normal	Moderat	

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KUBOTA GRAVEMASKINER MED LARVEBÅND K/KH/KX/U KX91-3S2 KUBOTA D1703-M-E3-BH (TIER 4I) (2007-2011)

**KØLESYSTEM**

Kapacitet: 7,3 liter (Radiator), Kapacitet: 1,6 liter (Reservetank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26*Skift alle 24 måneder***KØREREDUKTIONSENHED**

Kapacitet: 0,6 liter

ANVEND

Normal

KLIMA

Tropisk

PRODUKTANBEFALING 1

Gearlube HS GL-5 80W-140

PRODUKTANBEFALING 2

Gearlube GL-5 85W-140

PRODUKTANBEFALING 3

Unigear LS GL-3/GL-5 85W-140*Skift alle 500 timer/ 12 måneder*

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Skift alle 500 timer/ 12 måneder*

ANVEND

Første Service

KLIMA

Tropisk

PRODUKTANBEFALING 1

Gearlube HS GL-5 80W-140

PRODUKTANBEFALING 2

Gearlube GL-5 85W-140

PRODUKTANBEFALING 3

Unigear LS GL-3/GL-5 85W-140*Skift alle 100 timer*

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Skift alle 100 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.