

# KUBOTA GRAVEMASKINER MED LARVEBÅND K/KH/KX/U U10-3 KUBOTA D722-E-BH (2003 OG EFTER)



**MOTOR** Kubota D722  
Kapacitet: 2,2 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Tropisk |

PRODUKTANBEFALING 1

**Multifleet SCD 50**

*Kontroller alle 8 timer, skift alle 100 timer*

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Kroontrak MTH 10W-30**

PRODUKTANBEFALING 2

**Synfleet SHPD 10W-40**

PRODUKTANBEFALING 3

**Dieselfleet CD+ 15W-40**

*Kontroller alle 8 timer, skift alle 100 timer*

| ANVEND | KLIMA |
|--------|-------|
| Normal | Koldt |

PRODUKTANBEFALING 1

**Multifleet SCD 20W-20**

*Kontroller alle 8 timer, skift alle 100 timer*

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Arktisk |

PRODUKTANBEFALING 1

**Multifleet SCD 10W**

*Kontroller alle 8 timer, skift alle 100 timer*

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Tropisk |

PRODUKTANBEFALING 1

**Multifleet SCD 50**

*Skift alle 50 timer*

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

PRODUKTANBEFALING 1

**Kroontrak MTH 10W-30**

PRODUKTANBEFALING 2

**Synfleet SHPD 10W-40**

PRODUKTANBEFALING 3

**Dieselfleet CD+ 15W-40**

*Skift alle 50 timer*

| ANVEND         | KLIMA |
|----------------|-------|
| Første Service | Koldt |

PRODUKTANBEFALING 1

**Multifleet SCD 20W-20**

*Skift alle 50 timer*

# KUBOTA GRAVEMASKINER MED LARVEBÅND K/KH/KX/U U10-3 KUBOTA D722-E-BH (2003 OG EFTER)



| ANVEND                     |  | KLIMA   |
|----------------------------|--|---------|
| Første Service             |  | Arktisk |
| PRODUKTANBEFALING 1        |  |         |
| <b>Multifleet SCD 10W</b>  |  |         |
| <i>Skift alle 50 timer</i> |  |         |

| HYDRAULISK SYSTEM                                          |  |                  |
|------------------------------------------------------------|--|------------------|
| Kapacitet: 18 liter, Kapacitet: 12,5 liter (Hydrauliktank) |  |                  |
| ANVEND                                                     |  | KLIMA            |
| Normal                                                     |  | Middelhavsagtigt |
| PRODUKTANBEFALING 1                                        |  |                  |
| <b>Perlus H 68</b>                                         |  |                  |
| <i>Kontroller alle 10 timer, skift alle 1000 timer</i>     |  |                  |

| ANVEND                                                 |                     | KLIMA |
|--------------------------------------------------------|---------------------|-------|
| Normal                                                 |                     | Koldt |
| PRODUKTANBEFALING 1                                    | PRODUKTANBEFALING 2 |       |
| <b>Perlus H 46</b>                                     | <b>Perlus H 32</b>  |       |
| <i>Kontroller alle 10 timer, skift alle 1000 timer</i> |                     |       |

| ANVEND                                                |  | KLIMA            |
|-------------------------------------------------------|--|------------------|
| 20-40% Brug af hydraulikhammer                        |  | Middelhavsagtigt |
| PRODUKTANBEFALING 1                                   |  |                  |
| <b>Perlus H 68</b>                                    |  |                  |
| <i>Kontroller alle 10 timer, skift alle 800 timer</i> |  |                  |

| ANVEND                                                |                     | KLIMA |
|-------------------------------------------------------|---------------------|-------|
| 20-40% Brug af hydraulikhammer                        |                     | Koldt |
| PRODUKTANBEFALING 1                                   | PRODUKTANBEFALING 2 |       |
| <b>Perlus H 46</b>                                    | <b>Perlus H 32</b>  |       |
| <i>Kontroller alle 10 timer, skift alle 800 timer</i> |                     |       |

| ANVEND                                                |  | KLIMA            |
|-------------------------------------------------------|--|------------------|
| 40-60% Brug af hydraulikhammer                        |  | Middelhavsagtigt |
| PRODUKTANBEFALING 1                                   |  |                  |
| <b>Perlus H 68</b>                                    |  |                  |
| <i>Kontroller alle 10 timer, skift alle 400 timer</i> |  |                  |

| ANVEND                                                |                     | KLIMA |
|-------------------------------------------------------|---------------------|-------|
| 40-60% Brug af hydraulikhammer                        |                     | Koldt |
| PRODUKTANBEFALING 1                                   | PRODUKTANBEFALING 2 |       |
| <b>Perlus H 46</b>                                    | <b>Perlus H 32</b>  |       |
| <i>Kontroller alle 10 timer, skift alle 400 timer</i> |                     |       |

# KUBOTA GRAVEMASKINER MED LARVEBÅND K/KH/KX/U U10-3 KUBOTA D722-E-BH (2003 OG EFTER)



| ANVEND                         |  | KLIMA            |
|--------------------------------|--|------------------|
| 60-80% Brug af hydraulikhammer |  | Middelhavsagtigt |
| PRODUKTANBEFALING 1            |  |                  |
| <b>Perlus H 68</b>             |  |                  |

Kontroller alle 10 timer, skift alle 300 timer

| ANVEND                         |                     | KLIMA |
|--------------------------------|---------------------|-------|
| 60-80% Brug af hydraulikhammer |                     | Koldt |
| PRODUKTANBEFALING 1            | PRODUKTANBEFALING 2 |       |
| <b>Perlus H 46</b>             | <b>Perlus H 32</b>  |       |

Kontroller alle 10 timer, skift alle 300 timer

| ANVEND                          |  | KLIMA            |
|---------------------------------|--|------------------|
| 80-100% Brug af hydraulikhammer |  | Middelhavsagtigt |
| PRODUKTANBEFALING 1             |  |                  |
| <b>Perlus H 68</b>              |  |                  |

Kontroller alle 10 timer, skift alle 200 timer

| ANVEND                          |                     | KLIMA |
|---------------------------------|---------------------|-------|
| 80-100% Brug af hydraulikhammer |                     | Koldt |
| PRODUKTANBEFALING 1             | PRODUKTANBEFALING 2 |       |
| <b>Perlus H 46</b>              | <b>Perlus H 32</b>  |       |

Kontroller alle 10 timer, skift alle 200 timer

| SMØREPUNKTER/NIPLER  |                                 |                              |
|----------------------|---------------------------------|------------------------------|
| ANVEND               |                                 | KLIMA                        |
| Normal               |                                 | Moderat                      |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

| KØLESYSTEM                    |                     |         |
|-------------------------------|---------------------|---------|
| Kapacitet: 3,5 liter          |                     |         |
| ANVEND                        |                     | KLIMA   |
| Normal                        |                     | Moderat |
| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2 |         |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>  |         |

Kontroller alle 10 timer, skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.