

KUBOTA GRAVEMASKINER MED LARVEBÅND K/KH/KX/U U25-3A



MOTOR

Kapacitet: 4,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SHPD 15W-40

Skift alle 250 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SHPD 15W-40

Skift alle 50 timer

HYDRAULISK SYSTEM

Kapacitet: 37 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Perlus H 68

Skift alle 1000 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 46

Skift alle 1000 timer

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Perlus H 32

Skift alle 1000 timer

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KUBOTA GRAVEMASKINER MED LARVEBÅND K/KH/KX/U U25-3A



KØLESYSTEM

Kapacitet: 3 liter (Radiator), Kapacitet: 0,6 liter (Reservetank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Skift alle 24 måneder

KØREREDUKTIONSENHED

Kapacitet: 0,35 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 500 timer

LARVEBÅNDSRULLER

Kapacitet: 0,08 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30

RULLER FOR

Kapacitet: 0,07 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30

ØVRE RULLER

Kapacitet: 0,06 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.