

# KUBOTA GUMMIHJULSLÆSSERE R/RT R420S KUBOTA D1503-M-T-E2 (2004-2013)



**MOTOR** Kubota D1503-M-T-E2  
Kapacitet: 7 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3           |
|-----------------------------|-----------------------------|-------------------------------|
| <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> | <b>Multifleet SHPD 10W-40</b> |

*Skift alle 250 timer/ 6 måneder*

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3           |
|-----------------------------|-----------------------------|-------------------------------|
| <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> | <b>Multifleet SHPD 10W-40</b> |

*Skift alle 50 timer*

**DIFFERENTIALE BAG**  
Kapacitet: 3 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2 |  |
|--------------------------|---------------------|--|
| <b>Agrifluid HT-Plus</b> | <b>Agrifluid HT</b> |  |

*Kontroller alle 500 timer, skift alle 1000 timer*

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2 |  |
|--------------------------|---------------------|--|
| <b>Agrifluid HT-Plus</b> | <b>Agrifluid HT</b> |  |

*Skift alle 500 timer*

**DIFFERENTIALE FOR**  
Kapacitet: 3 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2 |  |
|--------------------------|---------------------|--|
| <b>Agrifluid HT-Plus</b> | <b>Agrifluid HT</b> |  |

*Kontroller alle 500 timer, skift alle 1000 timer*

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2 |  |
|--------------------------|---------------------|--|
| <b>Agrifluid HT-Plus</b> | <b>Agrifluid HT</b> |  |

*Skift alle 500 timer*

# KUBOTA GUMMIHJULSLÆSSERE R/RT R420S KUBOTA D1503-M-T-E2 (2004-2013)



## HYDRAULISK SYSTEM

Kapacitet: 42 liter (Hydrauliktank), Kapacitet: 60 liter (Samlet systemvolumen)

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3           |
|-----------------------------|-----------------------------|-------------------------------|
| <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

Skift alle 1000 timer

| ANVEND         | KLIMA            |
|----------------|------------------|
| Første Service | Middelhavsagtigt |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3           |
|-----------------------------|-----------------------------|-------------------------------|
| <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

Skift alle 500 timer

## HYDRAULISK BREMSESYSTEM

Kapacitet: 0,3 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 |  |  |
|---------------------|--|--|
| <b>Perlus H 32</b>  |  |  |

## SMØREPUNKTER/NIPLER

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
|----------------------|---------------------------------|------------------------------|
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

| ANVEND | KLIMA |
|--------|-------|
| Normal | Koldt |

| PRODUKTANBEFALING 1     |  |  |
|-------------------------|--|--|
| <b>Gear Grease EP 1</b> |  |  |

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Arktisk |

| PRODUKTANBEFALING 1     |  |  |
|-------------------------|--|--|
| <b>Gear Grease EP 0</b> |  |  |

# KUBOTA GUMMIHJULSLÆSSERE R/RT R420S KUBOTA D1503-M-T-E2 (2004-2013)



## KØLESYSTEM

Kapacitet: 6,5 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

### PRODUKTANBEFALING 2

**Coolant -26**

*Kontroller alle 10 timer, skift alle 24 måneder*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*