

LIEBHERR GRAVEMASKINER MED HJUL A A900 (166) DEUTZ F4L-912



MOTOR Deutz F4L-912
Kapacitet: 9,7 liter

ANVEND	KLIMA
Normal, svovlniveau i brændstof <0,5 %, omgivelsestemperatur <-10° C	Middelhavsagtigt

PRODUKTANBEFALING 1		
Multifleet SHPD 20W-50		

Kontroller alle 10 timer, skift alle 250 timer/ 12 måneder

ANVEND	KLIMA
Normal, svovlniveau i brændstof <0,5 %, omgivelsestemperatur <-10° C	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak CVT 10W-40	Helar 0W-40	Agridiesel CRD+ 15W-40

Kontroller alle 10 timer, skift alle 250 timer/ 12 måneder

ANVEND	KLIMA
Normal, svovlniveau i brændstof <0,5 %, omgivelsestemperatur >-10° C	Middelhavsagtigt

PRODUKTANBEFALING 1		
Multifleet SHPD 20W-50		

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

ANVEND	KLIMA
Normal, svovlniveau i brændstof <0,5 %, omgivelsestemperatur >-10° C	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak CVT 10W-40	Helar 0W-40	Agridiesel CRD+ 15W-40

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

DIFFERENTIALE SELVSPÆRRENDE
Kapacitet: 6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

DIFFERENTIALE UBEGRÆNSET SLIP
Kapacitet: 1,4 liter (hvert nav)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

LIEBHERR GRAVEMASKINER MED HJUL A A900 (166) DEUTZ F4L-912



GEAR

Kapacitet: 7,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

Gearlube GL-4 80W

NAVREDUKTIONER "LIMITED SLIP"

Kapacitet: 1,4 liter (hvert nav)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

NAVREDUKTIONER IKKE-"LIMITED SLIP"

Kapacitet: 7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

HYDRAULISK SYSTEM

Kapacitet: 250 liter (Hydrauliksystem inkl. tank), Kapacitet: 210 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Synfleet SHPD 10W-40

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

HT Q9 High Grade Grease

PRODUKTANBEFALING 2

Labora Grease

PRODUKTANBEFALING 3

Q5 MP Calcep Grease EP 2

LIEBHERR GRAVEMASKINER MED HJUL A A900 (166) DEUTZ F4L-912



SVINGREDUKTIONSENHED

Kapacitet: 10 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

Gearlube GL-4 80W

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.