

LIEBHERR KRANER MED LARVEBÅND, WIREBETJENT HS HS895HD OM444LA (1998 OG EFTER)



MOTOR Mercedes-Benz OM444LA
Kapacitet: 41,5 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Kontroller alle 8 timer, skift alle 500 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40	

Kontroller alle 8 timer, skift alle 500 timer

REDUKTIONSGEARKASSE
Kapacitet: 13,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 8 timer, skift alle 500 timer

HYDRAULISK SYSTEM
Kapacitet: 1100 liter (Hydrauliktank)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Kontroller alle 8 timer, skift alle 2000 timer

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
HT Q9 High Grade Grease	Labora Grease	Q5 MP Calcep Grease EP 2

SMØRINGSPUNKTER & NIPLER SVINGGEAR

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

LIEBHERR KRANER MED LARVEBÅND, WIREBETJENT HS HS895HD OM444LA (1998 OG EFTER)



KØLESYSTEM

Kapacitet: 80 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 11

PRODUKTANBEFALING 2

Coolant -38 Organic NF

PRODUKTANBEFALING 3

Coolant -26

KØREREDUKTIONSENHED

Kapacitet: 34 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 500 timer, skift alle 1000 timer

SPILBEGRÆNSNINGSENHED

Kapacitet: 30 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 500 timer, skift alle 1000 timer

SPILBEGRÆNSNINGSENHED ANTI-DREJNING

Kapacitet: 1,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 500 timer, skift alle 1000 timer

SPILBEGRÆNSNINGSENHED HOVEDBOOMKONTROL

Kapacitet: 7,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 500 timer, skift alle 1000 timer

LIEBHERR KRANER MED LARVEBÅND, WIREBETJENT HS HS895HD OM444LA (1998 OG EFTER)


SPILBEGRÆNSNINGSENHED LØFTEKABEL TIL HEJS

Kapacitet: 0,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Kontroller alle 500 timer, skift alle 1000 timer*
SVINGREDUKTIONSENHED

Kapacitet: 11,2 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Kontroller alle 500 timer, skift alle 1000 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.