

LINDE CONTAINERBETJENING (313-SERIE) C80/3 PERKINS 1106C-E60TA



MOTOR Perkins 1006.6T
Kapacitet: 15,5 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 40	HDX 40	

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
HDX 20W-50	HDX 30	HDX 20W-20

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Kroontrak MTH 10W-30		

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

ANVEND	KLIMA
Første Service	Tropisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 40	HDX 40	

Skift alle 50 timer

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
HDX 20W-50	HDX 30	HDX 20W-20

Skift alle 50 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1		
Kroontrak MTH 10W-30		

Skift alle 50 timer

LINDE CONTAINERBETJENING (313-SERIE) C80/3 PERKINS 1106C-E60TA



DRIVAKSELGEAR

Kapacitet: 24,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140

Kontroller alle 500 timer, skift alle 2000 timer

GEAR POWERSHIFT 3/3

Kapacitet: 15 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 10W

PRODUKTANBEFALING 2

ATF Dexron II-D

Kontroller alle 10 timer, skift alle 1000 timer

NAVREDUKTIONER

Kapacitet: 1,5 liter (hvert nav)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140

Kontroller alle 500 timer, skift alle 2000 timer

HYDRAULISK SYSTEM

Kapacitet: 305 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 46

PRODUKTANBEFALING 2

Perlus H 68

PRODUKTANBEFALING 3

Perlus AF 46

Kontroller alle 10 timer, skift alle 3000 timer

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 2

MP Lithep Grease EP 2

LINDE CONTAINERBETJENING (313-SERIE) C80/3 PERKINS 1106C-E60TA



KØLESYSTEM

Kapacitet: 25 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 10 timer, skift alle 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.