

LINDE GAFFELTRUCKS, DIESEL (393-SERIEN) H25D (2010-2015)



MOTOR CBHA
Kapacitet: 4,5 liter

ANVEND	KLIMA
Foretrukket, udvided	Moderat

PRODUKTANBEFALING 1		
Helar SP LL-03 5W-30		

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

HYDRAULISK SYSTEM

Kapacitet: 25,5 liter (Lifthøjde: 5000-6,900 mm), Kapacitet: 28 liter (Lifthøjde: 6900-8000 mm), Kapacitet: 24 liter (Lifthøjde: op til 5000 mm)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 68	Perlus AF 68	

Kontroller alle 1000 timer/ 12 måneder, skift alle 6000 timer/ 72 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 68	Perlus AF 100	

Kontroller alle 1000 timer/ 12 måneder, skift alle 6000 timer/ 72 måneder

ANVEND	KLIMA
Biologisk nedbrydelig olie	Moderat

PRODUKTANBEFALING 1		
Perlus Biosynth 46		

Kontroller alle 1000 timer/ 12 måneder, skift alle 6000 timer/ 72 måneder

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
MoS2 Grease EP 2		

LINDE GAFFELTRUCKS, DIESEL (393-SERIEN) H25D (2010-2015)



KØLESYSTEM

Kapacitet: 9 liter, Kapacitet: 11 liter (+ klimaanlæg + varmer)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 12

Skift alle 9000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.