

LULL SPOREDE SKOVANHÆNGERE 6K-37 CUMMINS 4BT3.9



MOTOR Cummins 4BT3.9

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40

DIFFERENTIALE BAG Kapacitet: 12,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

DIFFERENTIALE FOR Kapacitet: 12,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

LULL SPOREDE SKOVANHÆNGERE 6K-37

CUMMINS 4BT3.9

**GEAR POWERSHIFT 4/3**

Kapacitet: 16 liter (Komplet), Kapacitet: 10,4 liter (Servicepåfyldning)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Synfleet SHPD 10W-40

PRODUKTANBEFALING 2

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3

Multifleet SHPD 10W-40

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Agrifluid HT**NAVREDUKTIONER BAG**

Kapacitet: 1,7 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

NAVREDUKTIONER FOR

Kapacitet: 1,7 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

HYDRAULISK SYSTEM

Kapacitet: 166,3 liter (Hydrauliktank), Kapacitet: 245,7 liter (Komplet)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 32**SMØREPUNKTER/NIPLER**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

LULL SPOREDE SKOVANHÆNGERE 6K-37 CUMMINS 4BT3.9



KØLESYSTEM

Kapacitet: 17 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.