

MAEDA MINILARVEFODSKRAN MC-285C YANMAR 2TNE68-MB (S/N P00001 ->)



MOTOR Yanmar 2TNE68
Kapacitet: 2,3 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 500 timer

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Dieselfleet CD+ 15W-40

Skift alle 500 timer

ANVEND
Normal

KLIMA
Koldt

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 500 timer

ANVEND
Første Service

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 250 timer

ANVEND
Første Service

KLIMA
Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Dieselfleet CD+ 15W-40

Skift alle 250 timer

ANVEND
Første Service

KLIMA
Koldt

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 250 timer

MAEDA MINILARVEFODSKRAN MC-285C YANMAR 2TNE68-MB (S/N P00001 ->)



SPILBEGRÆNSNING

Kapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Abacot MEP 320

Kontroller alle 100 timer, skift alle 1000 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Abacot MEP 320

Skift alle 250 timer

HYDRAULISK SYSTEM

Kapacitet: 20 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 46

PRODUKTANBEFALING 2

Perlus H 32

PRODUKTANBEFALING 3

Perlus H 22

Skift alle 1000 timer

ANVEND

Første Service

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Perlus H 46

Skift alle 50 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 32

PRODUKTANBEFALING 2

Perlus H 22

Skift alle 50 timer

KØLESYSTEM

Kapacitet: 2,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

MAEDA MINILARVEFODSKRAN MC-285C

YANMAR 2TNE68-MB (S/N P00001 ->)

**KØREREDUKTIONSENHED**

Kapacitet: 0,33 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Abacot MEP 320*Kontroller alle 250 timer, skift alle 1000 timer*

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Abacot MEP 320*Skift alle 250 timer***SVINGREDUKTIONSENHED**

Kapacitet: 0,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Abacot MEP 320*Skift alle 1000 timer*

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Abacot MEP 320*Skift alle 250 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.