

MANITOU GAFFELTRUCK M/MC M50-2T L CATERPILLAR C4.4T TIER III (S/N 757730 ->)



MOTOR C4.4
Kapacitet: 8,6 liter

ANVEND
Normal

KLIMA
Middelhavsgtigt

PRODUKTANBEFALING 1
Agridiesel MSP 15W-40

PRODUKTANBEFALING 2
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Kroontrak MTH 10W-30

PRODUKTANBEFALING 2
Synfleet SHPD 10W-40

PRODUKTANBEFALING 3
Armado Synth 5W-30

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

DIFFERENTIALE FOR Dana
Kapacitet: 6,8 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid HT-Plus

PRODUKTANBEFALING 2
Agrifluid HT

Kontroller alle 250 timer, skift alle 500 timer/ 12 måneder

ANVEND
Første Service

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid HT-Plus

PRODUKTANBEFALING 2
Agrifluid HT

Skift alle 50 timer

GEAR Turner 4/4 4/4
Kapacitet: 15,2 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Matic 2032

PRODUKTANBEFALING 2
ATF Almirol

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

ANVEND
Første Service

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Matic 2032

PRODUKTANBEFALING 2
ATF Almirol

Skift alle 50 timer

MANITOU GAFFELTRUCK M/MC M50-2T L CATERPILLAR C4.4T TIER III (S/N 757730 ->)



NAVREDUKTIONER FOR

Kapacitet: 0,76 liter (hvert nav)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 50 timer

HYDRAULISK SYSTEM

Kapacitet: 98,4 liter (Hydrauliktank)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Perlus H 46		

Kontroller alle 50 timer, skift alle 1000 timer/ 12 måneder

HYDRAULISK BREMSESYSTEM

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 2032	ATF Almirol	

Kontroller alle 50 timer, skift alle 1000 timer/ 12 måneder

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
MoS2 Grease EP 2		

MANITOU GAFFELTRUCK M/MC M50-2T L CATERPILLAR C4.4T TIER III (S/N 757730 ->)



KØLESYSTEM

Kapacitet: 18,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.