

MANITOU GAFFELTRUCK MI MI 18 G NISSAN K21 (856888 ->) (2014 OG EFTER)



MOTOR Nissan K21
Kapacitet: 3,8 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Synfleet SHPD 10W-40

PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40

Kontroller alle 10 timer, skift alle 500 timer/ 6 måneder

ANVEND
Første Service

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Synfleet SHPD 10W-40

PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40

Skift alle 50 timer

DIFFERENTIALE
Kapacitet: 5,8 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

Kontroller alle 250 timer, skift alle 2000 timer/ 24 måneder

GEAR
Kapacitet: 4 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Matic 2032

PRODUKTANBEFALING 2
ATF Almirol

Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder

HYDRAULISK SYSTEM
Kapacitet: 40 liter (Hydrauliktank)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Perlus Biosynth 32

PRODUKTANBEFALING 2
Perlus H 32

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

MANITOU GAFFELTRUCK MI MI 18 G NISSAN K21 (856888 ->) (2014 OG EFTER)



HYDRAULISK BREMSESYSTEM

Kapacitet: 1,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

KØLESYSTEM

Kapacitet: 11 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.