

MANITOU GAFFELTRUCK MSI MSI 20 G BUGGIE TOYOTA 4Y (<-139125) (KASSE 2001)



MOTOR Toyota 4Y
Kapacitet: 4 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3
Multifleet SHPD 15W-40

DREJELED TIL AKSEL BAG

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Labora Grease

PRODUKTANBEFALING 2
Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3
MP Lithep Grease EP 2

NAVREDUKTIONER FOR

Kapacitet: 1,1 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-4 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

HYDRAULISK SYSTEM

Kapacitet: 95 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Perlus H 46

SMØREPUNKTER/NIPLER ANDRE

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Labora Grease

PRODUKTANBEFALING 2
Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3
MP Lithep Grease EP 2

MANITOU GAFFELTRUCK MSI MSI 20 G BUGGIE TOYOTA 4Y (<-139125) (KASSE 2001)



SMØREPUNKTER/NIPLER TELESKOPARMLED

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Q7 MP Calcep Grease WR 2	PRODUKTANBEFALING 2 Caliplex HD Grease EP 2	PRODUKTANBEFALING 3 Q5 MP Calcep Grease EP 2

SMØREPUNKTER/NIPLER VIPPECYLINDERFOD

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Q7 MP Calcep Grease WR 2	PRODUKTANBEFALING 2 Caliplex HD Grease EP 2	PRODUKTANBEFALING 3 Q5 MP Calcep Grease EP 2

KØLESYSTEM

Kapacitet: 11 liter

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Coolant SP 15+	PRODUKTANBEFALING 2 Coolant SP 12	PRODUKTANBEFALING 3 Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.