

MANITOU GAFFELTRUCK S-TC S402TC-D FORD 192 CI



MOTOR Ford 192 CI
Kapacitet: 6,65 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2
Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 150 timer

DIFFERENTIALE FOR
Kapacitet: 45,9 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Kroontrak CVT 10W-40

PRODUKTANBEFALING 2
Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 3
Agrifluid HT-Plus

Skift alle 1200 timer

GEAR POWERSHIFT 4/4
Kapacitet: 18 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
ATF-A

Kontroller alle 150 timer, skift alle 600 timer

HYDRAULISK SYSTEM
Kapacitet: 67,8 liter (Hydrauliktank)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Perlus H 46

Kontroller alle 10 timer, skift alle 600 timer

HYDRAULISK SYSTEM STYRING

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Kroontrak CVT 10W-40

PRODUKTANBEFALING 2
Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 3
Agrifluid HT-Plus

MANITOU GAFFELTRUCK S-TC S402TC-D

FORD 192 CI



SMØREPUNKTER/NIPLER GENERELT

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

SMØREPUNKTER/NIPLER HJULLEJER BAG

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

Skift alle 600 timer

KØLESYSTEM

Kapacitet: 10,5 liter

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Coolant -38 Organic NF	PRODUKTANBEFALING 2 Coolant -26	

Kontroller alle 10 timer

TELESKOPARMKÆDER

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Dieselfleet CD+ 15W-40	PRODUKTANBEFALING 2 Multifleet SHPD 15W-40	

Kontroller alle 10 timer, skift alle 300 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.